

Marlow®

DATASHEET

S.P.I.E WPX Floating Rope

Marlow's floating extraction system allows easier retrieval from waterborne operations.



- Designed to carry 10 to 12 personnel
- 2 loop colour coded integrated safety system for all personnel
- 1 Yellow Loop for easy retrieval.
- Floats allowing easier retrieval from water operations
- Super strong & light-weight – the main rope has been designed for low shock loads

Applications:

- Standard length 40 metres - Part Number: TAU013
- Insertion & extraction

Material:

Main rope:

Manufactured from Polyolefin

Hardwearing

Lightweight (floats)

Very high elongation (low shock loads)

Personnel Loops:

Manufactured from UHMPE

UHMPE (ultra high modulus polyethylene)

Very lightweight - more than 8 x lighter than steel wire for a given strength

High strength - 80% stronger than steel wire for a given weight

Low stretch - see table below

Good resistance to chemicals and UV

Zero water absorption & shrinkage (floats)

Construction:

Physical properties:

Relative density: 0.93 (floats)

Chemical resistance: Excellent resistance to most chemicals (additional info available on request)

UV resistance: Good

Melting point: 140 °C

Critical temperature: 80 °C (exposure to temperatures over this will result in permanent strength loss)

Terminations

Spliced eye termination: Soft eye splice as standard

DIAMETER		MASS		AVERAGE STRENGTH			MINIMUM STRENGTH		
mm	inch	g/m	lb/100ft	kg	lb	kN	kg	lb	kN
MAIN ROPE									
30	1 12/64	495.5	33.23	16880	37136	165.6	15100	33300	148.1
PERSONAL & SAFETY LOOPS									
10	13/32	48.6	3.26	3860	8492	37.9	3860	8492	37.9

Marlow Ropes Ltd
Ropemaker Park
Diplocks Way
Hailsham
East Sussex
BN27 3GU
England

Phone: +44 (0) 1323 444444
Fax: +44 (0) 1323 444455
e-mail: sales@marlowropes.com
Web: www.marlowropes.com



Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied.

Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose.

Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines.

Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.